
2019

QUALIKO

PROFESSIONAL LIGHT COMPONENTS

NEXT

QUALIKO srl
PROFESSIONAL LIGHT COMPONENTS



Lampade LED Cemento • LED Concrete lamps

NEXT Lampade LED Cemento • LED Concrete lamps

Made in Italy



11kWh/1000h

INDOOR IP20

CE IP20 EMC RoHS

Type	Part N°	Input (V)	Power (W)	Lumen	Light Colour	°Kelvin (±10%)	CRI	Dimensions (mm)	Packing box dimensions (mm)	Weight (kg)
NEXT	**BWC8521LEDNW**	100÷250 AC	11±1	1210	NW	4000°K	>80	178X147X125h	230x180x210h	1,20
NEXT	**BWC8521LEDWW**	100÷250 AC	11±1	1190	WW	3000°K	>80	178X147X125h	230x180x210h	1,20


Applique LED
- Struttura in Cemento
- Grande omogeneità luminosa
- Funziona in bassa tensione con trasformatore incorporato
- Consumo molto limitato
- Lunga durata

LED wall lamp
- Structure in Concrete
- Homogeneous light output
- Safety low voltage with specific included driver
- Limited consumption
- Long life time

LED Wandleuchte
- Struktur in Beton
- Homogenes Licht
- NV-Betrieb durch besonderen Transformator
- Begrenzter Verbrauch
- Lange Lebensdauer

Applique LED
- Corps en Ciment
- Luminosité très homogène
- Il marche en basse tension avec alimentation integrée
- Consommation tres limitée
- Longue durée de vie

Lamparas de pared LED
- Estructura de Cemento
- Excelente homogeneidad luminica
- Alta seguridad por funcionamiento a baja tension, con transformador integrado
- Consumo muy limitado- Larga vida



PAGE

QUALIKO srl
PROFESSIONAL LIGHT COMPONENTS



Lampade LED Cemento • LED Concrete lamps

PAGE Lampade LED Cemento • LED Concrete lamps

Made in Italy



8kWh/1000h

INDOOR IP20

CE IP20 EMC RoHS

Type	Part N°	Input (V)	Power (W)	Lumen	Light Colour	°Kelvin (±10%)	CRI	Dimensions (mm)	Packing box dimensions (mm)	Weight (kg)
PAGE NW	**BWC8523LEDNW**	100÷250 AC	8±1	1030	NW	4000°K	>80	152x118x200h	250x200x210h	0,90
PAGE WW	**BWC8523LEDWW**	100÷250 AC	8±1	970	WW	3000°K	>80	152x118x200h	250x200x210h	0,90


Applique LED
- Struttura in Cemento
- Grande omogeneità luminosa
- Funziona in bassa tensione con trasformatore incorporato
- Consumo molto limitato
- Lunga durata

LED wall lamp
- Structure in Concrete
- Homogeneous light output
- Safety low voltage with specific included driver
- Limited consumption
- Long life time

LED Wandleuchte
- Struktur in Beton
- Homogenes Licht
- NV-Betrieb durch besonderen Transformator
- Begrenzter Verbrauch
- Lange Lebensdauer


Applique LED
- Corps en Ciment
- Luminosité très homogène
- Il marche en basse tension avec alimentation integrée
- Consommation tres limitée
- Longue durée de vie

Lamparas de pared LED
- Estructura de Cemento
- Excelente homogeneidad luminica
- Alta seguridad por funcionamiento a baja tension, con transformador integrado
- Consumo muy limitado- Larga vida



FOLD


QUALIKO srl
PROFESSIONAL LIGHT COMPONENTS



Lampade LED Cemento • LED Concrete lamps

FOLD Lampade LED Cemento • LED Concrete lamps

Made in Italy



31kWh/1000h

INDOOR IP54 OUTDOOR

CE IP54 EMC RoHS

Type	Part N°	Input (V)	Power (W)	Lumen	Light Colour	°Kelvin (±10%)	CRI	Dimensions (mm)	Packing box dimensions (mm)	Weight (kg)
FOLD LARGE	**BWC8422LEDNW**	100÷250 AC	31±1	3800	NW	4000°K	>80	135x300x300h	380x370x160h	3,00
FOLD LARGE	**BWC8422LEDWW**	100÷250 AC	31±1	3650	WW	3000°K	>80	135x300x300h	380x370x160h	3,00


Applique LED
- Struttura in Cemento
- Grande omogeneità luminosa
- Funziona in bassa tensione con trasformatore incorporato
- Consumo molto limitato
- Lunga durata

LED wall lamp
- Structure in Concrete
- Homogeneous light output
- Safety low voltage with specific included driver
- Limited consumption
- Long life time

LED Wandleuchte
- Struktur in Beton
- Homogenes Licht
- NV-Betrieb durch besonderen Transformator
- Begrenzter Verbrauch
- Lange Lebensdauer

Applique LED
- Corps en Ciment
- Luminosité très homogène
- Il marche en basse tension avec alimentation integrée
- Consommation tres limitée
- Longue durée de vie

Lamparas de pared LED
- Estructura de Cemento
- Excelente homogeneidad luminica
- Alta seguridad por funcionamiento a baja tension, con transformador integrado
- Consumo muy limitado- Larga vida



FRAME




Lampade LED Cemento • LED Concrete lamps

FRAME Lampade LED Cemento • LED Concrete lamps

Made in Italy







CE IP54 EMC RoHS

Type	Part N°	Input (V)	Power (W)	Lumen	Light Colour	°Kelvin (±10%)	CRI	Dimensions (mm)	Packing box dimensions (mm)	Weight (kg)
FRAME SQ	**BWC8438LEDNW**	100÷250 AC	8±1	930	NW	4000°K	>80	222x150x50h	265x210x110h	1,30
FRAME SQ	**BWC8438LEDWW**	100÷250 AC	8±1	890	WW	3000°K	>80	222x150x50h	265x210x110h	1,30


Applique LED
- Struttura in Cemento
- Grande omogeneità luminosa
- Funziona in bassa tensione con trasformatore incorporato
- Consumo molto limitato
- Lunga durata

LED wall lamp
- Structure in Concrete
- Homogeneous light output
- Safety low voltage with specific included driver
- Limited consumption
- Long life time


LED Wandleuchte
- Struktur in Beton
- Homogenes Licht
- NV-Betrieb durch besonderen Transformator
- Begrenzter Verbrauch
- Lange Lebensdauer

Applique LED
- Corps en Ciment
- Luminosité très homogène
- Il marche en basse tension avec alimentation integrée
- Consommation tres limitée
- Longue durée de vie

Lamparas de pared LED
- Estructura de Cemento
- Excelente homogeneidad luminica
- Alta seguridad por funcionamiento a baja tension, con transformador integrado
- Consumo muy limitado
- Larga vida



FRAME SQUARE





BRICK

QUALIKO srl
PROFESSIONAL LIGHT COMPONENTS




Lampade LED Cemento • LED Concrete lamps

BRICK Lampade LED Cemento • LED Concrete lamps

Made in Italy







CE IP54 EMC RoHS

Type	Part N°	Input (V)	Power (W)	Lumen	Light Colour	°Kelvin (±10%)	CRI	Dimensions (mm)	Packing box dimensions (mm)	Weight (kg)
BRICK	**BWC8211LEDNW**	100÷250 AC	12±1	1310	NW	4000°K	>80	275x94x57h	340x150x120h	1,30
BRICK	**BWC8211LEDWW**	100÷250 AC	12±1	1250	WW	3000°K	>80	275x94x57h	340x150x120h	1,30


Applique LED
- Struttura in Cemento
- Grande omogeneità luminosa
- Funziona in bassa tensione con trasformatore incorporato
- Consumo molto limitato
- Lunga durata


LED wall lamp
- Structure in Concrete
- Homogeneous light output
- Safety low voltage with specific included driver
- Limited consumption
- Long life time

LED Wandleuchte
- Struktur in Beton
- Homogenes Licht
- NV-Betrieb durch besonderen Transformator
- Begrenzter Verbrauch
- Lange Lebensdauer

Applique LED
- Corps en Ciment
- Luminosité très homogène
- Il marche en basse tension avec alimentation integrée
- Consommation tres limitée
- Longue durée de vie

Lamparas de pared LED
- Estructura de Cemento
- Excelente homogeneidad luminica
- Alta seguridad por funcionamiento a baja tension, con transformador integrado
- Consumo muy limitado- Larga vida





LOGOS

QUALIKO srl
PROFESSIONAL LIGHT COMPONENTS




Lampade LED Cemento • LED Concrete lamps

LOGOS Lampade LED Cemento • LED Concrete lamps

Made in Italy







CE IP54 EMC RoHS

Type	Part N°	Input (V)	Power (W)	Lumen	Light Colour	°Kelvin (±10%)	CRI	Dimensions (mm)	Packing box dimensions (mm)	Weight (kg)
LOGOS	**BWC8339LEDNW**	100÷250 AC	8±1	940	NW	4000°K	>80	125x125x59h	170x170x110h	1,00
LOGOS	**BWC8339LEDWW**	100÷250 AC	8±1	890	WW	3000°K	>80	125x125x59h	170x170x110h	1,00


Applique LED
- Struttura in Cemento
- Grande omogeneità luminosa
- Funziona in bassa tensione con trasformatore incorporato
- Consumo molto limitato
- Lunga durata

LED wall lamp
- Structure in Concrete
- Homogeneous light output
- Safety low voltage with specific included driver
- Limited consumption
- Long life time

LED Wandleuchte
- Struktur in Beton
- Homogenes Licht
- NV-Betrieb durch besonderen Transformator
- Begrenzter Verbrauch
- Lange Lebensdauer

Applique LED
- Corps en Ciment
- Luminosité très homogène
- Il marche en basse tension avec alimentation integrée
- Consommation tres limitée
- Longue durée de vie

Lamparas de pared LED
- Estructura de Cemento
- Excelente homogeneidad luminica
- Alta seguridad por funcionamiento a baja tension, con transformador integrado
- Consumo muy limitado- Larga vida





CHRONOS

QUALIKO srl
PROFESSIONAL LIGHT COMPONENTS




Lampade LED Cemento • LED Concrete lamps

CHRONOS Lampade LED Cemento • LED Concrete lamps

QUALIKO srl

Made in Italy







CE IP54 EMC RoHS

Type	Part N°	Input (V)	Power (W)	Lumen	Light Colour	°Kelvin (±10%)	CRI	Dimensions (mm)	Packing box dimensions (mm)	Weight (kg)
CHRONOS	**BWC8440LEDNW**	100÷250 AC	8±1	940	NW	4000°K	>80	Ø155x59h	200x200x130h	1,00
CHRONOS	**BWC8440LEDWW**	100÷250 AC	8±1	890	WW	3000°K	>80	Ø155x59h	200x200x130h	1,00


Applique LED
- Struttura in Cemento
- Grande omogeneità luminosa
- Funziona in bassa tensione con trasformatore incorporato
- Consumo molto limitato
- Lunga durata


LED wall lamp
- Structure in Concrete
- Homogeneous light output
- Safety low voltage with specific included driver
- Limited consumption
- Long life time

LED Wandleuchte
- Struktur in Beton
- Homogenes Licht
- NV-Betrieb durch besonderen Transformator
- Begrenzter Verbrauch
- Lange Lebensdauer

Applique LED
- Corps en Ciment
- Luminosité très homogène
- Il marche en basse tension avec alimentation integrée
- Consommation tres limitée
- Longue durée de vie

Lamparas de pared LED
- Estructura de Cemento
- Excelente homogeneidad luminica
- Alta seguridad por funcionamiento a baja tension, con transformador integrado
- Consumo muy limitado- Larga vida





BOB

QUALIKO srl
PROFESSIONAL LIGHT COMPONENTS




Lampade LED Cemento • LED Concrete lamps

BOB Lampade LED Cemento • LED Concrete lamps

Made in Italy








CE IP54 EMC RoHS

Type	Part N°	Input (V)	Power (W)	Lumen	Light Colour	°Kelvin (±10%)	CRI	Dimensions (mm)	Packing box dimensions (mm)	Weight (kg)
BOB	**BWC8417LEDWW**	100÷250 AC	7±1	350	WW	3000°K	>80	150x125x100h	210x200x180h	1,47



Applique LED
- Struttura in Cemento
- Grande omogeneità luminosa
- Funziona in bassa tensione con trasformatore incorporato
- Consumo molto limitato
- Lunga durata

LED wall lamp
- Structure in Concrete
- Homogeneous light output
- Safety low voltage with specific included driver
- Limited consumption
- Long life time

LED Wandleuchte
- Struktur in Beton
- Homogenes Licht
- NV-Betrieb durch besonderen Transformator
- Begrenzter Verbrauch
- Lange Lebensdauer

Applique LED
- Corps en Ciment
- Luminosité très homogène
- Il marche en basse tension avec alimentation integrée
- Consommation tres limitée
- Longue durée de vie

Lamparas de pared LED
- Estructura de Cemento
- Excelente homogeneidad luminica
- Alta seguridad por funcionamiento a baja tension, con transformador integrado
- Consumo muy limitado- Larga vida



ARCH & NEEDLE

QUALIKO srl
PROFESSIONAL LIGHT COMPONENTS



Lampade LED Cemento da Giardino

LED Concrete Garden Lamps

ARCH & NEEDLE Lampade LED Cemento da Giardino
LED Concrete Garden Lamps

Made in Italy



ARCH



NEEDLE LARGE



NEEDLE SMALL

CE IP65 EMC RoHS

Type	Part N°	Input (V)	Power (W)	Lumen	Light Colour	°Kelvin (±10%)	CRI	Dimensions (mm)	Packing box dimensions (mm)	Weight (kg)
ARCH	**BGL70047WW0C**	100÷240 AC	8,5	800	WW	3000°K	>80	295x140x690h	470x330x840h	32
NEEDLE LARGE	**BGL70037WW0C**	100÷240 AC	8,5	800	WW	3000°K	>80	295x95x735h	470x280x850h	25
NEEDLE SMALL	**BGL70027WW0C**	100÷240 AC	8,5	800	WW	3000°K	>80	295x95x490h	470x290x600h	17

Lampade LED da giardino IP65
- Struttura in Cemento
- Funziona in bassa tensione con trasformatore incorporato
- Consumo molto limitato
- Lunga durata

IP65 LED garden lamps
- Structure in Concrete
- Safety low voltage with specific included driver
- Limited consumption
- Long life time

IP65 LED Gartenleuchten
- Struktur in Beton
- NV-Betrieb durch besonderen Transformator
- Begrenzter Verbrauch
- Lange Lebensdauer

Lampes LED IP65 pour le jardin
- Corps en Ciment
- Il marche en basse tension avec alimentation integrée
- Consommation tres limitée
- Longue durée de vie

Lamparas LED IP65 por el jardin
- Estructura de Cemento
- Alta seguridad por funcionamiento a baja tension, con transformador integrado
- Consumo muy limitado- Larga vida

THESIS & ANGLE

QUALIKO srl
PROFESSIONAL LIGHT COMPONENTS



Lampade LED Cemento da Giardino

LED Concrete Garden Lamps

THESIS & ANGLE Lampade LED Cemento da Giardino
LED Concrete Garden Lamps

Made in Italy



ANGLE LARGE



ANGLE SMALL



THESIS

CE IP65 EMC RoHS

Type	Part N°	Input (V)	Power (W)	Lumen	Light Colour	°Kelvin (±10%)	CRI	Dimensions (mm)	Packing box dimensions (mm)	Weight (kg)
ANGLE LARGE	**BGL70067WW0C**	100÷240 AC	8,5	800	WW	3000°K	>80	110x110x740h	260x250x830h	10
ANGLE SMALL	**BGL70057WW0C**	100÷240 AC	8,5	800	WW	3000°K	>80	110x110x500h	260x25x580h	7
THESIS	**BGL70017WW0C**	100÷240 AC	8,5	800	WW	3000°K	>80	160x120x640h	310x270x710h	10

Lampade LED da giardino IP65
- Struttura in Cemento
- Funziona in bassa tensione con trasformatore incorporato
- Consumo molto limitato
- Lunga durata

IP65 LED garden lamps
- Structure in Concrete
- Safety low voltage with specific included driver
- Limited consumption
- Long life time

IP65 LED Gartenleuchten
- Struktur in Beton
- NV-Betrieb durch besonderen Transformator
- Begrenzter Verbrauch
- Lange Lebensdauer

Lampes LED IP65 pour le jardin
- Corps en Ciment
- Il marche en basse tension avec alimentation integrée
- Consommation tres limitée
- Longue durée de vie

Lamparas LED IP65 por el jardin
- Estructura de Cemento
- Alta seguridad por funcionamiento a baja tension, con transformador integrado
- Consumo muy limitado- Larga vida