QUALIKO

PROFESSIONAL LIGHT COMPONENTS

2020



SQUARE

Incasso LED quadrato extrapiatto
- LED ad alta efficienza

Square extra flat recessed LED downlight
- High efficiency LED

24 Volt Safety Voltage

INDOOR IP52

Vedere pagina 186 per i kit che includono il driver LED - See page 186 for kits including LED driver

RAL 9010

Type	Part N°	Dimensions (mm)	Colour	°Kelvin	Lumen	Power (W)	Installation hole (mm)	Packing box dimensions (mm)	Weight (kg)
SQUARE 100 NW	**BD10024QNW1B**	100x100x28h	Natural White	4200°K	303	6	90x90	200x190x60h	0,26
SQUARE 100 WW	**BD10024QWW1B**	100x100x28h	Warm White	3000°K	286	6	90x90	200x190x60h	0,26
SQUARE 150 NW	**BD15024QNW1B**	150x150x28h	Natural White	4200°K	727	11	125x125	250x240x60h	0,46
SQUARE 150 WW	**BD15024QWW1B**	150x150x28h	Warm White	3000°K	686	11	125x125	250x240x60h	0,46
SQUARE 180 NW	**BD18024QNW1B**	180x180x28h	Natural White	4200°K	1134	17	160x160	270x260x60h	0,59
SQUARE 180 WW	**BD18024QWW1B**	180x180x28h	Warm White	4200°K	1070	17	160x160	270x260x60h	0,59



MIST

Incasso LED tondo alta potenza IP65
- LED ad alta efficienza

Round IP65 high power recessed LED downlight
- High efficiency LED

INDOOR IP65 OUTDOOR

Vedere pagina 186 per i kit che includono il driver LED - See page 186 for kits including LED driver

Type	Part N°	Dimensions (mm)	Colour	Lumen (Lm)	Voltage Max (V)	Current Max (mA)	Beam °	Power Max (W)	Installation hole (mm)	Packing box dimensions (mm)	Weight (kg)
MIST SMALL NW	**BDCL103A08NB**	Ø 80x30h	NW 4000°K	863	38	185	60°	8	Ø 70	115x110x75	0,25
MIST SMALL WW	**BDCL103A08WB**	Ø 80x30h	WW 3000°K	760	38	185	60°	8	Ø 70	115x110x75	0,25
MIST LARGE NW	**BDCL103A13NB**	Ø 110x50h	NW 4000°K	1318	38	300	60°	13	Ø 95	135x125x110	0,45
MIST LARGE WW	**BDCL103A13WB**	Ø 110x50h	WW 3000°K	1180	38	300	60°	13	Ø 95	135x125x110	0,45



POP

Incasso a LED tondo ad alta potenza
- Installazione semplice e veloce - Funziona direttamente a tensione di rete con alimentatore incorporato - Lunga durata

INDOOR IP20

Round extra powerful recessed LED downlight
- Easy and quick installation - Works directly with mains voltage (Built-in driver) - Long life time

Type	Part N°	Dimensions (mm)	Colour	Lumen (Lm)	Input V	Beam °	Power Max (W)	Installation hole (mm)	Packing box dimensions (mm)	Weight (kg)
POP 115 NW	**BDL11508NW0B**	Ø 115x69h	NW 4000°K	750	100÷240	100°	8	Ø 95	120x120x78h	0,20
POP 145 NW	**BDL14510NW0B**	Ø 145x79h	NW 4000°K	900	100÷240	100°	10	Ø 125	150x150x92h	0,25
POP 175 NW	**BDL17513NW0B**	Ø 175x85h	NW 4000°K	1200	100÷240	100°	13	Ø 150	180x180x96h	0,35
POP 145 WW	**BDL14510WW0B**	Ø 145x79h	WW 3000°K	850	100÷240	100°	10	Ø 125	150x150x92h	0,25
POP 175 WW	**BDL17513WW0B**	Ø 175x85h	WW 3000°K	1150	100÷240	100°	13	Ø 150	180x180x96h	0,35